



Specially Designed for Drilling FIBERGLASS PANELS and Boards.



FRP CORE BIT (CARBIDE TEETH)



Maximum
DRILLING DEPTH
IS
1-3/4"!!

NEW!



*Item No.
PCSKL716HEX

Characteristics

- Quick change system easily locks and unlocks cutter from shank.
- The only bit of its kind specially designed for drilling Fiberglass panels and boards.
- Carbide teeth for fast, burr-free cutting; highly resistant to over-heating, and at the same time does not require any coolant.

For use in

- Fiberglass, FRP, acrylic resin fiber, vinyl chloride, composite walling, wood.
- Drilling holes in wood (up to 2x) against concrete.

Specifications

- Dia. 25/32" (20mm) - 5" (127mm)
- Max. drilling depth: 1-3/4" (45mm)
- Long shank (8") available for deeper drilling.
- Shank dia : Poly-clic shank "S" / "L"
S shank : 25/32" (20mm) - 1-3/4" (45mm).
L shank : 2" (50mm) - 5" (127mm).

MIYANAGA
ISO 9001/14001 Certified
<http://www.miyanagaamerica.com/>

Size Table

Cutter

The actual sizes are in metric. (US\$)

Nominal dia. (Inch)	Nominal dia. (mm)	Cutter	
		Part-No.	Sugg. List
3/4	20	PCFRP020C	39.80
7/8	22	PCFRP022C	
15/16	24	PCFRP024C	
1	25	PCFRP025C	50.28
1-3/32	28	PCFRP028C	
1-1/8	29	PCFRP029C	
1-3/16	30	PCFRP030C	62.84
1-1/4	32	PCFRP032C	
1-19/64	33	PCFRP033C	
1-3/8	35	PCFRP035C	75.40
1-1/2	38	PCFRP038C	
1-9/16	40	PCFRP040C	
1-3/4	45	PCFRP045C	84.84
2	50	PCFRP050C	99.48
2-1/8	55	PCFRP055C	112.06
2-3/8	60	PCFRP060C	120.44
2-9/16	65	PCFRP065C	136.16
2-3/4	70	PCFRP070C	144.52
2-7/8	75	PCFRP075C	151.84
3-1/8	80	PCFRP080C	160.22
3-1/2	90	PCFRP090C	184.32
3-3/4	95	PCFRP095C	197.92
3-7/8	100	PCFRP100C	213.64
4-1/4	110	PCFRP110C	239.84
4-1/2	115	PCFRP115C	259.72
4-3/4	120	PCFRP120C	280.68
5	127	PCFRP127C	298.46

Shank

(US\$)

Poly-clic shank	Part No.	Sugg. List	For use with
S Shank	PCSKS	47.64	1" - 1-3/4" (25mm - 45mm)
S Shank SDS	PCSKSR		
S Shank 200L(8")	PCSKS200	57.60	2" - 8-1/4" (50mm - 210mm)
S Shank SDS 200L(8")	PCSKSR200		
L Shank	PCSKL	85.66	2" - 8-1/4" (50mm - 210mm)
L Shank SDS	PCSKLR		
L Shank 200L(8")	PCSKL200	102.62	2" - 8-1/4" (50mm - 210mm)
L Shank SDS 200L(8")	PCSKLR200		
L Shank with 7/16" Hex	PCSKL716HEX	90.00	
SDS-max Shank(Rotary mode)	PCSKXMXK	141.38	
Dust Cap for S Shank	PCBCS	2.60	For S Shank
Dust Cap for L Shank	PCBCL	2.60	For L Shank

Center Drill

(US\$)

Item	Part-No.	Sugg. List
Center drill	PCFRPCDS	17.06
Center drill	PCFRPCDL	23.56

Recommended Drill Speed/ Wattage

Diameter inch (mm)	rpm	W
25/32 - 2 (20-50)	600 - 1300	over 500W
2-1/8 - 3-7/8 (55-100)	500 - 1000	over 600W
4-1/4 - 5 (110-127)	250 - 800	over 700W

 **MIYANAGA America Corp.**

1010 W. Republic Dr. Unit 1
Addison, Illinois 60101 USA
Tel:(630)359-5795 Fax:(630)359-5806
<http://www.miyanagaamerica.com/>



MIYANAGA CO.,LTD

Registered office and Factory-Japan
Representative Office-Europe

