

DRILLING IN REINFORCED CONCRETE
QUICK-CHANGE SYSTEM
EASY SLUG REMOVAL



New to the Poly-clic Series,
"Wet Type Diamond Core Bit"!

Use only with Wetmond shank and Wetmond Center-Pin.

Characteristics

- Convenient drilling in reinforced concrete with only rotary mode.
- Central water feed system allows effective cooling of the blade edge and smooth discharge of dust.

For use in

- Concrete, reinforced concrete, brick, mortar, stone, ceramic tile, marble, granite, hume & clay pipes, Porcelain Tile etc.

Specifications

- Dia : 1"(25mm) - 8-5/8"(220mm)
- Max. drilling depth : 6"(150mm)
(Cutter body length : 7"(180mm))
- Shank dia : Poly Clic Wet shank "S" or "L"
S shank : 1"(25mm) - 1-3/4"(45mm) dia..
L shank : 2"(50mm) - 8-5/8"(220mm) dia.
- Center pin : Center pin for Wetmond Core Bit
Part No. : PCWDCP

Size Table

Cutter

(US\$)

Nominal dia. (Inch)	Nominal dia. (mm)	Cutter	
		Part-No.	Sugg. List
1	25	PCWD25C	
1-1/8	29	PCWD29C	
1-1/4	32	PCWD32C	
1-3/8	35	PCWD35C	253.44
1/1/2	38	PCWD38C	
1/3/4	45	PCWD45C	
2	50	PCWD50C	280.64
2-1/8	55	PCWD55C	292.16
2-3/8	60	PCWD60C	302.66
2-9/16	65	PCWD65C	316.26
2-3/4	70	PCWD70C	344.54
2-7/8	75	PCWD75C	371.78
3-1/8	80	PCWD80C	399.00
3-1/2	90	PCWD90C	459.74
3-7/8	100	PCWD100C	522.56
4-3/4	120	PCWD120C	605.32
5-7/8	150	PCWD150C	715.26
6-3/4	170	PCWD170C	838.84
8-5/8	220	PCWD220C	1,121.60

Standard set comes with straight shank, SDS plus shank is optional.

Shank

(US\$)

Item	Part-No.	Sugg. List	For
Wet S shank	PCSKWDS	275.42	1 - 1-3/4 (25-45mm)
Wet S shank SDS	PCSKWDSR		
Wet S shank 300L	PCSKWDS30	289.02	
Wet S shank SDS 300L	PCSKWDSR30		
Wet L shank	PCSKWDL	316.26	2 - 8-5/8 (50-220mm)
Wet L shank SDS	PCSKWDLR		
Wet L shank 300L	PCSKWDL30	344.54	
Wet L shank SDS 300L	PCSKWDLR30		

Note; Use Poly-clic wet shank only with Wetmond Core Bit.
Please do not use with other Poly-clic cutter.

Center pin

(US\$)

	Part-No.	Sugg. List
Center pin	PCWDPCP	38.72

Caution; Supply water when drilling.
Due to use of water, possibility of electric shock.
Wear rubber gloves or use GFCIs.

DUST COLLECTING PAD

Features

- Cleaner work environment and improved efficiency
- Eliminates scattering of mine dust
- Compatible with products from other manufacturers
- Simple positioning



Application Example of Dust Collecting Pad

Traditional method Without Dust Collecting Pad
Dust is scattered, and cleaning takes more time than making holes.

Dust Collecting Pad

(US\$)

Part Number	Sugg. List	Description
SJP038	65.96	New Dust Collecting Pad "038" for Dia. 1-1/2" and below
SJP080	82.72	New Dust Collecting Pad "080" for Dia. 3-1/8" and below
SJPV	175.94	Dust Collecting Pad "V" for Dia. 6-1/2" and below
SJPL	226.20	Dust Collecting Pad "L" for Dia. 1-1/2" to 8-5/8"
SJP038P	8.48	Dust Collecting Adjust Plate for SJP038
SJP080P	10.44	Dust Collecting Adjust Plate for SJP080
SJPVA	27.52	Dust Collecting Adjust Plate V
SJPLA		Dust Collecting Adjust Plate L



MIYANAGA America Corp.

1010 W. Republic Dr. Unit 1
Addison, Illinois 60101 USA
Tel:(630)359-5795 Fax:(630)359-5806
<http://www.miyanagaamerica.com/>



MIYANAGA CO.,LTD

Registered office and Factory-Japan
Representative Office-Europe

