




Easy Drilling in Various Types of Siding Boards.



NEW!



*Item No.
PCSKL716HEX

A unique tip geometry which ensures safe cutting through nail embedded wood.



Characteristics

- Quick change system easily locks and unlocks cutter from shank.
- Specially designed for **safe** and fast drilling in nail embedded wood.
- Rotary only.
- Easy slug removal.

For use in

- Various types of Cement Siding and metallic siding, Nail embedded wood, FRP, PVC, and Artificial Marble.

Specifications

- Dia :1" (25mm) - 8-1/4" (210mm)
- Drilling depth : 5-1/8" (130mm)
- Long shank (8") available for deeper drilling.
- Shank dia : Poly-clic shank "S" / "L"
S shank : 1" (25mm) - 1-3/4" (45mm).
L shank : 2" (50mm) - 8-1/4" (210mm).

WOODING CORE BIT (CARBIDE TEETH)



MIYANAGA
ISO 9001/14001 Certified
<http://www.miyanagaamerica.com/>

WOODING CORE BIT (CARBIDE TEETH)



Size Table

Cutter

The actual sizes are in metric. (US\$)

Nominal dia.(Inch)	Nominal dia.(mm)	Cutter	
		Part-No.	Sugg. List
1	25	PCWS25C	
1-1/8	29	PCWS29C	
1-1/4	32	PCWS32C	57.60
1-3/8	35	PCWS35C	
1-1/2	38	PCWS38C	
1-3/4	45	PCWS45C	69.12
2	50	PCWS50C	71.20
2-1/8	55	PCWS55C	78.56
2-3/8	60	PCWS60C	80.64
2-9/16	65	PCWS65C	84.84
2-3/4	70	PCWS70C	97.40
2-7/8	75	PCWS75C	101.60
3-1/8	80	PCWS80C	103.68
3-1/2	90	PCWS90C	125.66
3-3/4	95	PCWS95C	130.92
3-7/8	100	PCWS100C	141.38
4-1/8	105	PCWS105C	146.62
4-3/4	120	PCWS120C	164.96
5-1/8	130	PCWS130C	209.44
6	155	PCWS155C	230.40
6-1/2	165	PCWS165C	248.74
7	180	PCWS180C	267.04
8-1/4	210	PCWS210C	412.64

Shank

(US\$)

Poly-clic shank	Part No.	Sugg. List	For use with	
S Shank	PCSKS	47.64	1" - 1-3/4" (25mm - 45mm)	
S Shank SDS	PCSKSR			
S Shank 200L(8")	PCSKS200	57.60		
S Shank SDS 200L(8")	PCSKSR200			
L Shank	PCSKL	85.66	2" - 8-1/4" (50mm - 210mm)	
L Shank SDS	PCSKLR			
L Shank 200L(8")	PCSKL200	102.62		
L Shank SDS 200L(8")	PCSKLR200			
L Shank with 7/16" Hex	PCSKL716HEX	90.00		
SDS-max Shank(Rotary mode)	PCSKXMXK	141.38		
Dust Cap for S Shank	PCBCS	2.60		For S Shank
Dust Cap for L Shank	PCBCL	2.60		For L Shank

Center drill

(US\$)

Item	Part-No.	Sugg. List
Center Drill	PCWSCD225	37.70

Recommended Drill Speed / Wattage

Diameter inch (mm)	rpm	W
1 - 1-3/4 (25-45)	800 - 1500	over 450W
2 - 3-1/8 (50-80)	700 - 1100	over 550W
3-3/8 - 4-3/4 (85-120)	700 - 1100	over 650W
5-1/8 - 8-3/4(130-220)	500 - 1100	over 750W

 **MIYANAGA America Corp.**

1010 W. Republic Dr. Unit 1
Addison, Illinois 60101 USA
Tel:(630)359-5795 Fax:(630)359-5806
<http://www.miyanagaamerica.com/>

MIYANAGA CO.,LTD

Registered office and Factory-Japan
Representative Office-Europe

