MIYANAGA

Poly-clic

WOODING CORE BIT (CARBIDE TEETH)

Easy Drilling in Various Types of Siding Boards.

NEW!

*Item No.
PCSKS716HEX
*Use PCSKL716HEX for cutters with 2" and up in diameter.

Demonstration Video

A unique tip geometry which ensures safe cutting through nail embedded wood.



Characteristics

- Quick change system easily locks and unlocks cutter from shank.
- Specially designed for **safe** and fast drilling in nail embedded wood.
- Rotary only.
- Easy slug removal.

For use in

- Various types of Cement Siding and metallic siding, Nail embedded wood, FRP, PVC, and Artificial Marble.

Specifications

- Dia :1" (25mm) - 8-1/4" (210mm)
- Drilling depth : 5-1/8" (130mm)
- Long shank (8") available for deeper drilling.
- Shank dia : Poly-clic shank "S" / "L"
  S shank : 1" (25mm) - 1-3/4" (45mm).
  L shank : 2" (50mm) - 8-1/4" (210mm).

MIYANAGA

ISO 9001/14001 Certified

http://www.miyanagaamerica.com/

WOODING CORE BIT (CARBIDE TEETH)

MIYANAGA

Size Table

Cutter

The actual sizes are in metric.

(US$)

Nominal dia.(Inch)	Nominal dia.(mm)	Cutter	
		Part-No.	Sugg. List
1	25	PCWS25C	
1-1/8	29	PCWS29C	
1-1/4	32	PCWS32C	69.86
1-3/8	35	PCWS35C	
1-1/2	38	PCWS38C	
1-3/4	45	PCWS45C	84.28
2	50	PCWS50C	86.72
2-1/8	55	PCWS55C	95.12
2-3/8	60	PCWS60C	97.52
2-9/16	65	PCWS65C	103.54
2-3/4	70	PCWS70C	118.02
2-7/8	75	PCWS75C	122.84
3-1/8	80	PCWS80C	125.24
3-1/2	90	PCWS90C	151.74
3-3/4	95	PCWS95C	158.98
3-7/8	100	PCWS100C	171.00
4-1/8	105	PCWS105C	177.00
4-3/4	120	PCWS120C	199.90
5-1/8	130	PCWS130C	252.88
6	155	PCWS155C	278.20
6-1/2	165	PCWS165C	301.08
7	180	PCWS180C	322.74
8-1/4	210	PCWS210C	498.60

Shank

(US$)

Poly-clic shank	Part No.	Sugg. List	For use with
S Shank S Shank SDS	PCSKS PCSKSR	57.78	1" - 1-3/4" (25mm - 45mm)
S Shank 200L(8") S Shank SDS 200L(8")	PCSKS200 PCSKSR200	69.86	
S Shank with 7/16" Hex	PCSKS716HEX	96.60	
L Shank L Shank SDS	PCSKL PCSKLR	103.54	2" - 8-1/4" (50mm - 210mm)
L Shank 200L(8") L Shank SDS 200L(8")	PCSKL200 PCSKLR200	124.02	
L Shank with 7/16" Hex	PCSKL716HEX	115.00	
SDS-max Shank(Rotary mode)	PCSKXMXK	171.00	
Dust Cap for S Shank	PCBCS	3.24	For S Shank
Dust Cap for L Shank	PCBCL	3.24	For L Shank

Center drill

(US$)

Item	Part-No.	Sugg. List
Center Drill	PCWSCD225	45.74

Recommended Drill Speed / Wattage

Diameter inch (mm)	rpm	W
1 - 1-3/4 (25-45)	800 - 1500	over 450W
2 - 3-1/8 (50-80)	700 - 1100	over 550W
3-3/8 - 4-3/4 (85-120)	700 - 1100	over 650W
5-1/8 - 8-3/4(130-220)	500 - 1100	over 750W

MIYANAGA America Corp.

1010 W. Republic Dr. Unit 1
Addison, Illinois 60101 USA
Tel:(630)359-5795 Fax:(630)359-5806
http://www.miyanagaamerica.com/

MIYANAGA CO.,LTD
Registered office and Factory-Japan
Representative Office-Europe

STAFDA Associate